

Bowl cutter SM 45 T2M-R

Datasheet

| | | |
|--|----------------------------------|--|
| type code | 445 | |
| option model | standard | reinforced drive |
| Electrical data | | |
| operating voltage (standard) | 400V/50Hz | |
| rated power | 8,9 kW | 11,9 kW |
| obligatory pre-fusing at customer site ¹⁾ | 25 A gL/gG | 35 A gL/gG |
| rotation speed | | |
| knives head | 1200/2400 min ⁻¹ - | 1500/3000 min ⁻¹ 1800/3600 min ⁻¹ (optional) |
| mixing (forward and backward) | 75/150 min ⁻¹ | |
| bowl | 9/18 min ⁻¹ | |
| optimum batch size | | |
| boiled sausages | 36 kg | |
| cooked sausages | 32 kg | |
| raw sausages | 20 kg | |
| weight ⁵⁾ | 750 kg | 770 kg |

Bowl cutter SM 45 STL

Datasheet

| | |
|--|-----------------------------|
| type code | 445 |
| Electrical data | |
| operating voltage (standard) | 400V/50Hz |
| rated power | 16 kW |
| obligatory pre-fusing at customer site ¹⁾ | 35 A gL/gG |
| leakage current @ 400V/50Hz typical/maximum at inrush (attend to use with residual current circuit breakers!) | 34/192mA |
| rotation speed | |
| Messerwellen-rotation speed | 40...4400 min ⁻¹ |
| Mischgang-rotation speed (vorwärts und rückwärts) | 40...500 min ⁻¹ |
| Schüsseldrehzahl | 9/18 min ⁻¹ |
| optimum batch size | |
| boiled sausages | 36 kg |
| cooked sausages | 32 kg |
| raw sausages | 20 kg |
| weight ⁵⁾ | 770 kg |