

## Cutmix CM 70 T2M-R

### Datasheet

<b>type code</b>	470	
<b>option model</b>	standard	reinforced drive
<b>Electrical data</b>		
operating voltage (standard)	400V/50Hz	
rated power	18,5 kW	22,3 kW
obligatory pre-fusing at customer site <sup>1)</sup>	50 A gL/gG	50 A gL/gG
<b>rotation speed</b>		
knives head	1500/3000 min <sup>-1</sup> -	1500/3000 min <sup>-1</sup> 1800/3600 min <sup>-1</sup> (optional)
mixing (forward and backward)	75/150 min <sup>-1</sup>	
bowl	9/18 min <sup>-1</sup>	
<b>optimum batch size</b>		
boiled sausages	56 kg	
cooked sausages	49 kg	
raw sausages	32 kg	
<b>weight<sup>5)</sup></b>		
without unloader	1140 kg	1160 kg
with unloader	1240 kg	1260 kg

## Cutmix CM 70 STL

### Datasheet

<b>type code</b>	470
<b>Electrical data</b>	
operating voltage (standard)	400V/50Hz
rated power	24,8 kW
obligatory pre-fusing at customer site <sup>1)</sup>	50 A gL/gG
leakage current @ 400V/50Hz typical/maximum at inrush (attend to use with residual current circuit breakers!)	34/192mA
<b>rotation speed</b>	
knives head	40...5000 min <sup>-1</sup>
mixing (forward and backward)	40...500 min <sup>-1</sup>
bowl drive (2-speed)	9/18 min <sup>-1</sup>
bowl drive (variable speed, optional)	5...18 min <sup>-1</sup>
<b>optimum batch size</b>	
boiled sausages	56 kg
cooked sausages	49 kg
raw sausages	32 kg
<b>weight<sup>5)</sup></b>	
without unloader	1150 kg
with unloader	1250 kg