

## Cutmix CM 90 T2M-R

### Datasheet

<b>type code</b>	490
<b>Electrical data</b>	
operating voltage (standard)	400V/50Hz
rated power	35 kW
obligatory pre-fusing at customer site <sup>1)</sup>	80 A gL/gG
<b>rotation speed</b>	
knives head	1500/3000 min <sup>-1</sup> 1800/3600 min <sup>-1</sup> (optional)
mixing (forward and backward)	75/150 min <sup>-1</sup>
bowl	9/18 min <sup>-1</sup>
<b>optimum batch size</b>	
boiled sausages	72 kg
cooked sausages	63 kg
raw sausages	41 kg
<b>weight<sup>5)</sup></b>	
without unloader	1220 kg
with unloader	1320 kg

## Cutmix CM 90 STL

### Datasheet

<b>type code</b>	490
<b>Electrical data</b>	
operating voltage (standard)	400V/50Hz
rated power	34,5 kW
obligatory pre-fusing at customer site <sup>1)</sup>	80 A gL/gG
leakage current @ 400V/50Hz typical/maximum at inrush (attend to use with residual current circuit breakers!)	34/192mA
<b>rotation speed</b>	
knives head	40...5000 min <sup>-1</sup>
mixing (forward and backward)	40...500 min <sup>-1</sup>
bowl drive	5...18 min <sup>-1</sup>
<b>optimum batch size</b>	
boiled sausages	72 kg
cooked sausages	63 kg
raw sausages	41 kg
<b>weight<sup>5)</sup></b>	
without unloader	1260 kg
with unloader	1360 kg